

**MSDS** Material Safety Data

**JorVel™**



**Jorgensen Laboratories, Inc.**  
1450 North Van Buren Avenue  
Loveland, CO 80538

Supermount  
Product Code J335x  
Review Date **SEP 15 2009**  
24 Hour Emergency Telephone:  
CMB: (800)535-5053

All non-emergency questions may be directed to customer service @ (970)669-2500 or fax (970)663-5042

**Supermount™**

**SECTION 1 PRODUCT IDENTIFICATION**

NAME: Supermount™ Coverslip Adhesive  
EKI ORDER NUMBERS: 7405  
SYNONYMS: Coverslip adhesive for microscopy, Mounting Media  
CAS NO: Does not apply  
FORMULA: Does not apply

\*\*\*\*LABEL HAZARD STATEMENT AND PRECAUTIONS\*\*\*\*

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION. Keep away from heat, sparks and flame. Avoid contact with skin, eyes and clothing. Avoid breathing vapor. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

**SECTION 2 HAZARDOUS INGREDIENTS / EXPOSURE LIMITS**

INGREDIENT/CAS NO	OSHA PEL	ACGIH TLV
Xylenes / 1330-20-7	100 ppm TWA	100 ppm TWA 150 ppm STEL
Terpene Resin Mixture / NA	N/E	N/E

Xylenes, 35% is subject to the reporting requirements of SARA 313 and 40CFR372

**SECTION 3 PHYSICAL / CHEMICAL CHARACTERISTICS**

SOLUBILITY IN WATER: Negligible  
VAPOR PRESSURE (mm Hg): 21  
SPECIFIC GRAVITY: 0.87  
EVAPORATION RATE: 0.6  
BOILING POINT: (C): 141  
VAPOR DENSITY: 3.7  
MELTING POINT: (C): N/A  
APPEARANCE AND ODOR: Clear, yellowish, sticky, viscous liquid. Sweet xylene odor.

**SECTION 4 FIRE / EXPLOSION HAZARD DATA**

FLASH POINT (C): N/E  
AUTOIGNITION TEMPERATURE (C): N/E  
FLAMMABLE LIMITS (%): UEL: N/E LEL: N/E  
EXTINGUISHING MEDIA: Water fog, foam dry chemical or CO2.

**SPECIAL FIRE FIGHTING PROCEDURES:** Firefighters should wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive-pressure mode.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Cool fire exposed containers with water to prevent vapor pressure buildup and container weakening.

---

## SECTION 5 REACTIVITY DATA

---

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Sources of ignition, heat.

**MATERIALS TO AVOID:** Strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** CO, CO<sub>2</sub>.

**HAZARDOUS POLYMERIZATION:** Does not occur.

---

## SECTION 6 HEALTH HAZARD DATA

---

**ROUTES OF ENTRY AND EFFECTS OF OVEREXPOSURE**

**INHALATION:** May cause nose and throat irritation.

**SKIN CONTACT:** May cause irritation.

**EYE CONTACT:** May cause irritation.

**SKIN ABSORPTION:** Kidney, liver damage.

**INGESTION:** Digestive tract irritation. Nervous system depression.

**CHRONIC:** Kidney, liver damage.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Asthma, skin sensitivity to xylenes, impaired lung function.

**CARCINOGENICITY:** None.

### \*\*\*FIRST AID PROCEDURES\*\*\*

**EYE CONTACT:** Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

**SKIN CONTACT:** Immediately flush with plenty of water for at least 15 minutes.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

**INGESTION:** Get immediate medical attention. Do NOT induce vomiting. If vomiting occurs, keep head below knees to avoid aspiration.

---

## SECTION 7 PRECAUTIONS FOR SAFE HANDLING AND USE

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:** Eliminate sources of ignition. Absorb with inert material and containerize for disposal.

**WASTE DISPOSAL METHOD:** Dispose in accordance with all applicable federal, state, and local environmental regulations.

**STORAGE:** Store tightly closed in approved "Flammable Liquids" storage area.

---

## SECTION 8 CONTROL MEASURES

---

**VENTILATION:** Local preferred.

**RESPIRATORY PROTECTION:** NIOSH approved respirator if OSHA Exposure Limits are exceeded.

**EYE PROTECTION:** Chemical splash safety goggles and/or full face shield.

**SKIN PROTECTION:** Xylene-proof gloves, lab coat and impervious apron.

---

**SECTION 9 OTHER INFORMATION**

---

**TRANSPORT (LAND, DOT)**

Xylenes, class 3 flammable, UN1307, packing group I I

**PRODUCT USE**

Laboratory use only

Jorgensen Laboratories, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. JORGENSEN LABORATORIES, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, JORGENSEN LABORATORIES, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.